DUCTLESS SYSTEMS

15 SEER SINGLE ZONE





Hand held remote includes many features like, I-Feel, X-Fan, and Sleep Mode.

- Available for installations in all regions (15 SEER)
- 9000, 12000, 18000, & 24000
 BTUH models available
- Quiet indoor operation (32-33 db)
- Hand held remote controller included
- Inverter driven (Variable Speed Compressor)
- Includes base pan heaters
- Blue Fin Coastal coating
- AHRI Certified Systems

5 YEAR BASE LIMITED PARTS WARRANTY / 10 YEAR REGISTERED PARTS WARRANTY

| Outdoor | Indoor | SEER | HSPF | EER | Capacity (BTUH) Cooling | Capacity (BTUH) Heating | Voltage | Gas Line | Liquid Line | Max Overcurrent Protection |
|----------------|----------------|------|------|------|-------------------------------|-------------------------------|--------------|-------------|----------------|----------------------------------|
| M4THS1509A11NB | M4MHW1509A1NOB | 15 | 9 | 10 | 9000 | 9500 | 208-230/60/1 | 3/8" | 1/4" | 15 |
| M4THS1512A11NB | M4MHW1512A1N0B | 15 | 9 | 9.25 | 12000 | 13000 | 208-230/60/1 | 3/8" | 1/4" | 15 |
| M4THS1518A11NB | M4MHW1518A1NOB | 15 | 9 | 9 | 17600 | 19000 | 208-230/60/1 | 1/2" | 1/4" | 25 |
| M4THS1524A11NB | M4MHW1524A1NOB | 15 | 9 | 9.75 | 22000 | 22800 | 208-230/60/1 | 5/8" | 1/4" | 25 |

15 SEER HP Singe Zone Ductless Systems

15 SEER AC Single Zone Ductless Systems

| Outdoor | Indoor | SEER | HSPF | EER | Capacity (BTUH) Cooling | Capacity (BTUH) Heating | Voltage | Gas Line | Liquid Line | Max Overcurrent Protection |
|----------------|----------------|------|------|------|-------------------------------|-------------------------------|--------------|-------------|----------------|----------------------------------|
| M4TCS1509A11NB | M4MCW1509A1N0B | 15 | - | 10 | 9000 | - | 208-230/60/1 | 3/8" | 1/4" | 15 |
| M4TCS1512A11NB | M4MCW1512A1N0B | 15 | - | 9.25 | 12000 | - | 208-230/60/1 | 3/8" | 1/4" | 15 |
| M4TCS1518A11NB | M4MCW1518A1N0B | 15 | - | 9 | 17600 | - | 208-230/60/1 | 1/2" | 1/4" | 25 |
| M4TCS1524A11NB | M4MCW1524A1N0B | 15 | - | 9.75 | 22000 | - | 208-230/60/1 | 5/8" | 1/4" | 25 |